



Image may differ from product. See technical specification for details.



HMV 180E

Hydraulic nut for mounting or dismounting of bearings

Facilitates easy and quick application of the high drive-up forces required for mounting bearings on tapered seatings. The hydraulic nut can also be used for dismounting bearings mounted on either adapter or withdrawal sleeves.

- Quick connection coupling can be fitted on the face or side of the nut
- A spare set of piston seals and maintenance kit is included
- Supplied with a quick connection coupling to fit the SKF hydraulic pumps
- Equipped with eyebolts, two tommy bars and four mating holes on their front face

개요

치수

연결 나사산	Tr 900×7
나사산 형태	ISO 2901-1977 tolerance class 7H
최대 피스톤 변위	30 mm
외부 직경	1 075 mm
피스톤 영역	124 100 mm ²
피스톤 내경	902 mm
피스톤 외경	1 043 mm
피스톤 너비	17 mm
너비	86 mm

성능

최대 압력	250 bar
Maximum pressure (MPa)	25 MPa

속성

유형	미터 표기 나사산
----	-----------

물류

제품 순 중량	210 kg
eClass 코드	23-05-19-01
UNSPSC 코드	73152101

호환 제품

예비 부품

빠른 연결 니플	729832 A
Spare O-ring set for Hydraulic nut (all versions)	HMV 180/233983
Spare nylon screw for Hydraulic nuts for size 70 and larger, 10 pcs	HMVE M5X17
Spare maintenance set for Hydraulic nuts, size 70 to 200	HMVM 70/200

액세서리

Feeler gauge	729865 A
Feeler gauge	729865 B

Horizontal dial gauge for Hydraulic nuts

[TMCD 1/2R](#)

For mounting with SKF drive-up method

Horizontal dial gauge for Hydraulic nuts

[TMCD 10R](#)

For mounting with SKF drive-up method

Vertical dial gauge for Hydraulic nuts

[TMCD 5P](#)

For mounting with SKF drive-up method

권장 제품

Hydraulic Pump for the SKF Drive-up Method for larger size
Hydraulic nuts

[TMJL 50DU](#)

For mounting with SKF drive-up method and dismantling

Hydraulic pump with large oil container

[TMJL 50](#)

For dismantling

Hydraulic pump with large oil container

[728619 E](#)

For dismantling

이용약관