




Image may differ from product. See technical specification for details.



HMV 38E

Hydraulic nut for mounting or dismounting of bearings

Facilitates easy and quick application of the high drive-up forces required for mounting bearings on tapered seatings. The hydraulic nut can also be used for dismounting bearings mounted on either adapter or withdrawal sleeves.

- Quick connection coupling can be fitted on the face or side of the nut
- A spare set of piston seals and maintenance kit is included
- Supplied with a quick connection coupling to fit the SKF hydraulic pumps
- Equipped with eyebolts, two tommy bars and four mating holes on their front face

개요

치수

| | |
|-----------|-------------------------------------|
| 연결 나사산 | M 190×3 |
| 나사산 형태 | ISO 965/111-1980 tolerance class 6H |
| 최대 피스톤 변위 | 7 mm |
| 외부 직경 | 270 mm |
| 피스톤 영역 | 11 500 mm ² |
| 피스톤 내경 | 191 mm |
| 피스톤 외경 | 259 mm |
| 피스톤 너비 | 8 mm |
| 너비 | 42 mm |

성능

| | |
|------------------------|---------|
| 최대 압력 | 800 bar |
| Maximum pressure (MPa) | 80 MPa |

속성

| | |
|----|-----------|
| 유형 | 미터 표기 나사산 |
|----|-----------|

물류

| | |
|-----------|-------------|
| 제품 순 중량 | 11.7 kg |
| eClass 코드 | 23-05-19-01 |
| UNSPSC 코드 | 73152101 |

호환 제품

예비 부품

| | |
|--|-------------------------------|
| 빠른 연결 니플 | 729832 A |
| Spare O-ring set for Hydraulic nut (all versions) | HMV 38/233983 |
| Spare nylon screws for Hydraulic nuts for sizes 10-69, 10pcs | HMVE M5X10 |
| Spare maintenance set for Hydraulic nuts, size 30 to 69 | HMVM 30/69 |

액세서리

| | |
|--|---------------------------|
| Feeler gauge | 729865 A |
| Feeler gauge | 729865 B |
| Horizontal dial gauge for Hydraulic nuts | TMCD 1/2R |

For mounting with SKF drive-up method

Horizontal dial gauge for Hydraulic nuts

[TMCD 10R](#)

For mounting with SKF drive-up method

Vertical dial gauge for Hydraulic nuts

[TMCD 5P](#)

For mounting with SKF drive-up method

권장 제품

Hydraulic Pump

[729124 DU](#)

For mounting with SKF drive-up method and dismantling

Hydraulic Pump for the SKF Drive-up Method for small to medium size Hydraulic nuts

[TMJL 100DU](#)

For mounting with SKF drive-up method and dismantling

유압 펌프

[729124](#)

For dismantling

Hydraulic pump with large oil container

[TMJL 100](#)

For dismantling

Hydraulic pump with large oil container

[728619 E](#)

For dismantling

이용약관