




Image may differ from product. See technical specification for details.



## HMV 56E

### Hydraulic nut for mounting or dismounting of bearings

Facilitates easy and quick application of the high drive-up forces required for mounting bearings on tapered seatings. The hydraulic nut can also be used for dismounting bearings mounted on either adapter or withdrawal sleeves.

- Quick connection coupling can be fitted on the face or side of the nut
- A spare set of piston seals and maintenance kit is included
- Supplied with a quick connection coupling to fit the SKF hydraulic pumps
- Equipped with eyebolts, two tommy bars and four mating holes on their front face

## 개요

### 치수

|           |                                  |
|-----------|----------------------------------|
| 연결 나사산    | Tr 280×4                         |
| 나사산 형태    | ISO 2901-1977 tolerance class 7H |
| 최대 피스톤 변위 | 12 mm                            |
| 외부 직경     | 380 mm                           |
| 피스톤 영역    | 21 100 mm <sup>2</sup>           |
| 피스톤 내경    | 282 mm                           |
| 피스톤 외경    | 363 mm                           |
| 피스톤 너비    | 9 mm                             |
| 너비        | 49 mm                            |

### 성능

|                        |         |
|------------------------|---------|
| 최대 압력                  | 800 bar |
| Maximum pressure (MPa) | 80 MPa  |

### 속성

|    |           |
|----|-----------|
| 유형 | 미터 표기 나사산 |
|----|-----------|

### 물류

|           |             |
|-----------|-------------|
| 제품 순 중량   | 23.3 kg     |
| eClass 코드 | 23-05-19-01 |
| UNSPSC 코드 | 73152101    |

## 호환 제품

### 예비 부품

|  |                               |
|--|-------------------------------|
| 빠른 연결 니플   | <a href="#">729832 A</a>      |
| Spare O-ring set for Hydraulic nut (all versions)            | <a href="#">HMV 56/233983</a> |
| Spare nylon screws for Hydraulic nuts for sizes 10-69, 10pcs | <a href="#">HMVE M5X10</a>    |
| Spare maintenance set for Hydraulic nuts, size 30 to 69      | <a href="#">HMVM 30/69</a>    |

### 액세서리

|  |                           |
|--|---------------------------|
| Feeler gauge                             | <a href="#">729865 A</a>  |
| Feeler gauge                             | <a href="#">729865 B</a>  |
| Horizontal dial gauge for Hydraulic nuts | <a href="#">TMCD 1/2R</a> |

*For mounting with SKF drive-up method*

---

Horizontal dial gauge for Hydraulic nuts

[TMCD 10R](#)

*For mounting with SKF drive-up method*

---

Vertical dial gauge for Hydraulic nuts

[TMCD 5P](#)

*For mounting with SKF drive-up method*

## 권장 제품

---

Hydraulic Pump for the SKF Drive-up Method for small to medium size Hydraulic nuts

[TMJL 100DU](#)

*For mounting with SKF drive-up method and dismantling*

---

Hydraulic pump with large oil container

[TMJL 100](#)

*For dismantling*

---

Hydraulic pump with large oil container

[728619 E](#)

*For dismantling*

이용약관