



Image may differ from product. See technical specification for details.

LAGF 18

Grease filler pump for use on drums

모범 윤활 관행에 따르면 각 유형의 그리스에는 개별 그리스 건이 필요하며 리필은 깨끗한 공정을 거쳐야 합니다. SKF 그리스 필러 펌프는 이러한 목표 달성을 위해 설계되었습니다. LAGF 18은 기계식 레버로 작동하며 18kg 드럼에서 그리스 건을 채울 때 최적의 청결함을 유지할 수 있습니다.

- 저압의 높은 스트로크 볼륨으로 빠른 충전, 모든 품목이 포함되어 있어 쉽게 사용할 수 있음, 모든 SKF 그리스에 대해 테스트 및 승인됨, SKF 베어링 패커 VKN 550과 함께 사용하기에 적합

개요

치수

적절한 드럼 내부 직경	265 - 285 mm
적절한 드럼 내부 높이(최대)	420 mm

성능

Maximum pressure (MPa)	3 MPa
최대 압력	30 bar

속성

권장 용도	그리스 건 또는 TLRD 그리스 디스펜서를 채우도록 설계된 드럼 또는 통용 그리스 필러 펌프
그리스 드럼 유형/크기용	18 kg 그리스 통
작동	핸들이 달린 수동 펌프
모빌리티	고정
윤활제 NLGI 등급(최대)	2
연결	윤활 지점: DIN 1283 니플
기압	-
스트로크당 용적	45 ml
호스	아니오
전원	수동
재료	강철
자재 처리	플라스틱 그립 포함 강철
주변 온도 범위	10 - 40 °C
권장 보관 온도	10 - 40 °C
상대 습도	< 65 %
내용	펌프 핸들이 있는 그리스 펌프, 드럼 커버 판, 드럼 팔로우 판

물류

제품 순 중량	4.12 kg
eClass 코드	23-06-91-06
UNSPSC 코드	15121902

호환 제품

액세서리

Grease trolley for grease drums/ pails, for Air-driven grease pumps	LAGT 18-50
Grease trolley for grease drums/ pails, for Air-driven grease pumps	LAGT 18-50F

권장 제품

Manual operated grease gun	TLGH 1
Manual operated grease gun	1077600
Manual operated grease gun	1077600 H
Manual operated grease gun set	1077600/SET
Manual operated grease gun, one handed	LAGH 400
Battery-driven grease guns	TLGB 20
Battery-driven grease guns	TLGB 20/110V
Battery driven grease gun	TLGB 1262-E
Battery driven grease gun	TLGB 1886-E

이용약관