



Image may differ from product. See technical specification for details.



## TMHP 30/170

Hydraulically-assisted heavy duty jaw puller with Hydraulic pump with large oil container

SKF 유압 보조 고강도 조 풀러 TMHP 30/170은 대형 베어링과 부품 탈착에 사용하는 강력한 풀러입니다. 자동식 센터링 풀러, 독특한 팬더그래프 시스템 및 핸들링 옵션이 있어 풀러를 안전하고 쉽게 사용할 수 있습니다. 스프인들과 유압 실린더의 조합으로 풀러를 빠르게 장착하는데 도움이 됩니다. SKF TMHP 30/170은 유압 펌프, 오일 및 연결부를 포함하여 바로 사용할 수 있는 완전한 세트 제공됩니다.

- 셀프 센터링 풀러를 사용하면 높은 당기는 힘을 쉽고 안전하게 적용할 수 있음, 스프인들과 유압 실린더의 조합을 통해 작업 길이를 쉽게 조정할 수 있음, 고유한 팬더그래프 시스템은 탁월한 그립감을 제공하고 작동 중 정렬 불량을 방지하는 데 도움이 됨, 리프팅 핸들과 아이 볼트를 사용한 간단한 조작, SKF 유압 펌프 TMJL 100, 유연한 고압 호스 및 유압 오일과 함께 즉시 사용 가능

## 개요

### 치수

외부 그림 너비	290 – 500 mm
암 유효 길이	170 mm
암 대체 길이	With accessory alternative arms: 350 or 600 mm
클로 높이	35 mm
암 전체 길이	508 mm
클로 길이	30 mm
클로 너비	24 mm
스핀들 헤드, 육각형 크기	28mm
스핀들 전체 길이	933 mm

### 속성

관장 용도	축에 간섭 끼움을 사용하여 산업, 건설 및 농업 응용 분야에서 더 큰 베어링, 기어, 풀리 및 기타 산업용 링 모양 부품을 분리하는 데 사용
원추형 시트(직선 축)에 공작물을 탈착하는 데 적합	예
테이퍼형 시트(원추형 축)에 베어링을 탈착하는 데 적합	예
슬리브에 베어링을 탈착하는 데 적합(어댑터 또는 인출 슬리브)	예
블라인드 배열(축이 있는 하우징)의 공작물 탈착에 적합	아니오
하우징에 공작물을 탈착하는 데 적합	아니오
베어링 유형(들)에 적합	전체
탈착력 생성	기계식 스프링이 장착된 이 풀러에서 유압 실린더의 피스톤을 전진시키려면 유압 펌프가 필요합니다. 유압 실린더에 연결할 권장 펌프 TMJL이 이 풀러에 포함되어 있습니다.
당김 힘(최대)	325 kN
암의 개수	3
유압 실린더, 피스톤 스트로크	50 mm
유압 실린더, 최대 작동 압력	800 bar
유압 실린더, 최대 작동 압력	80 MPa
유압 실린더, 오일 용량	204 cm <sup>3</sup>
스핀들 노즈 피스	예, ø33 mm
오일 점도(최대)	300 mm <sup>2</sup> /s
컬러	검은색
재료	금 엔지니어링 강철, 경화 및 강화 처리됨
코팅	화학적 흑색화됨
내용	1x 풀러 TMHP 30/170, 1x TMJL 100 펌프(목재 운반용 케이스에 포함), 1x 사용 지침 인쇄물, 1x 피스톤 고정 도구, 1x 목재 보관 상자

### 물류

제품 순 중량	76.4 kg
eClass 코드	23-05-19-01
UNSPSC 코드	27111712

## 호환 제품

### 재주입

Mounting or Dismounting fluid	<a href="#">LHMF 300/1</a>
-------------------------------	----------------------------

### 예비 부품

Spare arm for Hydraulically-assisted heavy duty jaw puller	<a href="#">3 x TMHP 30-1</a>
Spare spindle for Hydraulically-assisted heavy duty jaw puller	<a href="#">TMHP 30-5</a>

### 액세서리

Spare arm for Hydraulically-assisted heavy duty jaw puller	3 x TMHP 30-3
Extremely high viscosity bearing grease with solid lubricants	LGEV 2/0.035
Tri-section pulling plate	TMMS 260
Tri-section pulling plate	TMMS 380

## 권장 제품

Hydraulically-assisted heavy duty jaw puller without hydraulic pump	TMHP 30/170X
Hydraulically-assisted heavy duty jaw puller without hydraulic pump	TMHP 50/140X
Hydraulically-assisted heavy duty jaw puller without hydraulic pump	TMHP 50/320X
Hydraulically-assisted heavy duty jaw puller without hydraulic pump	TMHP 50/570X
Hydraulically-assisted heavy duty jaw puller without hydraulic pump	TMHP 30/350X
Hydraulically-assisted heavy duty jaw puller without hydraulic pump	TMHP 30/600X
Hydraulically-assisted heavy duty jaw puller without hydraulic pump	TMHP 15/260X
Hydraulically-assisted heavy duty jaw puller with Hydraulic pump with large oil container	TMHP 50/140
Hydraulically-assisted heavy duty jaw puller with Hydraulic pump with large oil container	TMHP 50/320
Hydraulically-assisted heavy duty jaw puller with Hydraulic pump with large oil container	TMHP 50/570
Hydraulically-assisted heavy duty jaw puller with Hydraulic pump with large oil container	TMHP 30/350
Hydraulically-assisted heavy duty jaw puller with Hydraulic pump with large oil container	TMHP 30/600
Hydraulically-assisted heavy duty jaw puller with Hydraulic pump with large oil container	TMHP 15/260

이용약관