
The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com (mailto:CustomerCAD@timken.com) • **Web site:** www.timken.com (http://www.timken.com)

Part Number 23968EMBW33, Spherical Roller Bearings - Brass Cage





Key Features

- Longer bearing life achieved from higher capacity (vs. competitors)
- Longer lubrication life achieved from lower operating temperatures due to reduced internal friction and running torque from cage guided rollers
- Better contaminant purging from slots on cage face helps extend bearing life

- Greater fatigue strength and increased wear resistance provide tougher protection against shock and acceleration loading from a brass cage

Key Dimensions

Bore (d)	340 mm
O.D. (D)	460 mm 18.1100 in
Width (B)	90 mm 3.543 in
Dynamic Radial Load Rating - 1M Revs (C1)	1670000 N 376000 lbf
e Factor[1]	0.17

Other Dimensions

Max Shaft Fillet Radius[2]	2.5 mm 0.100 in
Shaft Backing Shoulder Diameter	369.000 mm 14.5000 in
Housing Backing Shoulder Diameter	435 mm 17.1000 in
Design Unit	Metric

Ratings

Static Radial Load Rating (C0)	2990000 N 673000 lbf
Thermal Reference Speed - Grease	840 rpm
Thermal Reference Speed - Oil[3]	1000 rpm

Factors

Y0 Factor[4]	3.89
Y1 Factor [5]	3.98
Y2 Factor [6]	5.93
Geometry Factor (Cg) [7]	0.1306

[1] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

[2] Maximum housing fillet radius that bearing corners will clear.

[3] See thermal speed ratings in the engineering section.

[4] These factors apply for both inch and metric calculations. See engineering

[5] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

[6] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

[7] Geometry constant for Lubrication Life Adjustment Factor a3l.