The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com (mailto:CustomerCAD@timken.com) • **Web site:** www.timken.com (http://www.timken.com)

Part Number 23976EMBW507C08C2, Spherical Roller Bearings - Brass Cage





Key Features

- Longer bearing life achieved from higher capacity (vs. competitors)
- Longer lubrication life achieved from lower operating temperatures due to reduced internal friction and running torque from cage guided rollers
- Better contaminant purging from slots on cage face helps extend bearing life

- Greater fatigue strength and increased wear resistance provide tougher protection against shock and acceleration loading from a brass cage

Key Dimensions

Bore (d)	380 mm
O.D. (D)	520 mm 20.472 in
Width (B)	106 mm 4.1730 in
Dynamic Radial Load Rating - 1M Revs (C1)	2130000 N 479000 lbf
e Factor[1]	0.18

Other Dimensions

Max Shaft Fillet Radius[2]	3 mm 0.120 in
Shaft Backing Shoulder Diameter	416 mm 16.4000 in
Housing Backing Shoulder Diameter	488 mm 19.2000 in
Design Unit	Metric

Ratings

Static Radial Load Rating (C0)	3940000 N 886000 lbf
Thermal Reference Speed - Grease	740 rpm
Thermal Reference Speed - Oil[3]	870 rpm

Factors

Y0 Factor[4]	3.72
Y1 Factor [5]	3.8
Y2 Factor [6]	5.66
Geometry Factor (Cg) [7]	0.1405

[1] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

[2] Maximum housing fillet radius that bearing corners will clear.

[3] See thermal speed ratings in the engineering section.

[4] These factors apply for both inch and metric calculations. See engineering

[5] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

[6] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

[7] Geometry constant for Lubrication Life Adjustment Factor a3l.