
The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com (mailto:CustomerCAD@timken.com) • **Web site:** www.timken.com (http://www.timken.com)

Part Number 32060X, Tapered Roller Bearings - TS (Tapered Single) Metric





Key Features

- Available in single, double and multi-row configurations, as well as proprietary sizes
- Designed in collaboration with OE engineers to design, engineer and test bearings for premium performance in many applications
- Power dense designs allow for heavier loads and can help extend bearing life
- Optimized internal geometry lowers torque and operating temperatures to extend lubrication system life

- Can be designed to withstand high-corrosive, high-temperature and vacuum or low-lubrication environments with proprietary enhancements

Key Dimensions

Cone Part Number	X32060X
Cup Part Number	Y32060X
Bore (d)	300 mm 11.811 in
O.D. (D)	460 mm 18.1102 in
Width (T)	100.000 mm 3.937 in
Dynamic Radial Load Rating - 1M Revs (C1) [1]	1730000 N 389000 lbf
Dynamic Radial Load Rating - 90M Revs (C90) [2]	449000 N 101000 lbf
e Factor [3]	0.43
K Factor [4]	1.34
Series	32060X
Y Factor [5]	1.38

Other Dimensions

Inner Ring Width (B)	100 mm 3.937 in
Outer Ring Width (C)	74 mm 2.9134 in
Effective Center Location[6]	-1.8 mm -0.07 in
Max Shaft Fillet Radius[7]	5 mm 0.2 in
Max Housing Fillet Radius[8]	4 mm 0.16 in
Shaft Backing Shoulder Diameter - Frontface (da)	323 mm 12.72 in
Shaft Backing Shoulder Diameter - Backface (db)	336 mm 13.23 in
Housing Backing Shoulder Diameter - Frontface (Da)	439 mm 17.28 in
Housing Backing Shoulder Diameter - Backface (Db)	423 mm 16.65 in
Cage Location Relative to Backface (Aa)	11.7 mm 0.46 in
Cage Location Relative to Frontface (Ab)	6.9 mm 0.27 in
Weight	56.32 Kg 124.2 lb

Ratings

Dynamic Axial Rating - 90M Revs (Ca90)[9]	334000 N 75100 lbf
Static Radial Load Rating (C0)	3170000 N 712000 lbf

Factors

G1 Factor	2353.5
G2 Factor	203.9
Geometry Factor (Cg)[10]	0.189

[1] Based on 1 x 10^6 revolutions L_{10} life, for the ISO life calculation method.

[2] Based on 90 x 10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values.

[3] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

[4] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

[5] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

[6] Negative value indicates effective center inside cone backface.

[7] These maximum fillet radii will be cleared by the bearing corners.

[8] These maximum fillet radii will be cleared by the bearing corners.

[9] Based on 90 x 10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.

[10] Geometry constant for Lubrication Life Adjustment Factor a3l.