
The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com (mailto:CustomerCAD@timken.com) • **Web site:** www.timken.com (http://www.timken.com)

Part Number NCF1864V, Cylindrical Roller Radial Bearings - Full Complement





Key Features

- High radial load capacity
- Full-complement construction, no cage included
- Can manage axial loads in one direction and small axial displacement
- Sold as a completely unitized assembly
- Enhanced operational reliability due to optimized bearing design and reduced heat generation
- Long service life

Key Dimensions

Bore (d)	320 mm
O.D. (D)	400 mm 15.7480 in
Width (B)	1.4961 in 38 mm
Dynamic Radial Load Rating - 1M Revs (C1)[1]	471000 N 106000 lbf

Other Dimensions

Weight	10.6 Kg 23.400 lb
Shaft Backing Shoulder Dia.	340.8 mm 13.4200 in
Housing Backing Shoulder Dia.	383.8 mm 15.1100 in
Max Shaft Fillet Radius LF ID	0.060 in 1.5 mm
Max Shaft Fillet Radius RF ID	2.1 in 0.080 mm
Max Housing Fillet Radius LF OD	2.1 in 0.080 mm
Max Housing Fillet Radius RF OD	0.060 in 1.5 mm
DUR/DOR F/E	382.8 mm 15.0709 in
Permissible Axial Displacement (S3)[2]	3.00 mm 0.118 in

Ratings

Static Radial Load Rating (C0)	900000 N 202000 lbf
Thermal Reference Speed - Oil	700 rpm
Thermal Reference Speed - Grease	600 rpm

Factors

Geometry Factor (Cg)	0.167 0.1670 mm

[1] Based on 1 x 10^6 revolutions L_{10} life, for the ISO life calculation method.

[2] Permissible axial displacement from normal position of one bearing ring in relation to the other.