
The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com (mailto:CustomerCAD@timken.com) • **Web site:** www.timken.com (http://www.timken.com)

Part Number NCF2972V, Cylindrical Roller Radial Bearings - Full Complement





Key Features

- High radial load capacity
- Full-complement construction, no cage included
- Can manage axial loads in one direction and small axial displacement
- Sold as a completely unitized assembly
- Enhanced operational reliability due to optimized bearing design and reduced heat generation
- Long service life

Key Dimensions

Bore (d)	360 mm
O.D. (D)	480 mm 18.8976 in
Width (B)	2.8346 in 72 mm
Dynamic Radial Load Rating - 1M Revs (C1)[1]	1380000 N 310000 lbf

Other Dimensions

Weight	36.2 Kg 79.7 lb
Shaft Backing Shoulder Dia.	387.2 mm 15.24 in
Housing Backing Shoulder Dia.	454.3 mm 17.88 in
Max Shaft Fillet Radius LF ID	0.10 in 2.5 mm
Max Shaft Fillet Radius RF ID	3 in 0.12 mm
Max Housing Fillet Radius LF OD	3 in 0.12 mm
Max Housing Fillet Radius RF OD	0.10 in 2.5 mm
DUR/DOR F/E	451.2 mm 17.7638 in
Permissible Axial Displacement (S3)[2]	4.00 mm 0.158 in

Ratings

Static Radial Load Rating (C0)	2690000 N 604000 lbf
Thermal Reference Speed - Oil	440 rpm
Thermal Reference Speed - Grease	400 rpm

Factors

Geometry Factor (Cg)	0.2127 mm

[1] Based on 1 x 10^6 revolutions L_{10} life, for the ISO life calculation method.

[2] Permissible axial displacement from normal position of one bearing ring in relation to the other.