

The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com (mailto:CustomerCAD@timken.com) • **Web site:** www.timken.com (http://www.timken.com)

Part Number NU1026MA, Cylindrical Roller Radial Bearings - Single Row ISO





Key Features

- High radial load capacity
- Unique brass cage design for demanding applications
- Bearing can be separated for easier mounting and dismounting

- Design has a cylindrical inner ring and two ribs on the outer ring, making type NU bearings well suited for use as floating bearings
- Enhanced operational reliability
- Long service life

Key Dimensions

Bore (d)	130 mm
O.D. (D)	200 mm 7.874 in
Width (B)	1.2992 in 33 mm
Dynamic Radial Load Rating - 1M Revs (C1)[1]	197000 N 44300 lbf

Other Dimensions

Weight	7.2 Kg 15.8 lb
Shaft Backing Shoulder Diameter	142.6 mm 5.61 in
Housing Backing Shoulder Diameter	182 mm 7.717 in
Max Shaft Fillet Radius LF ID	2.0 in 0.080 mm
Max Shaft Fillet Radius RF ID	2 in 0.080 mm
Max Housing Fillet Radius LF OD	1.1 in 0.040 mm
Max Housing Fillet Radius RF OD	1.1 in 0.04 mm
Design Units	Metric
Type	NU

Ratings

Static Radial Load Rating (C0)	251000 N 56500 lbf
Thermal Reference Speed - Grease	3400 rpm
Thermal Reference Speed - Oil[2]	4200 rpm

Factors

Geometry Factor (Cg) [3]	0.104

[1] Based on 1 x 10^6 L_{10} life for the ISO life calculation method.

[2] See thermal speed ratings in the engineering section.

[3] Geometry constant for Lubrication Life Adjustment Factor a3l.