

The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com (mailto:CustomerCAD@timken.com) • **Web site:** www.timken.com (http://www.timken.com)

Part Number NU1032MAC3, Cylindrical Roller Radial Bearings - Single Row ISO





Key Features

- High radial load capacity
- Unique brass cage design for demanding applications
- Bearing can be separated for easier mounting and dismounting

- Design has a cylindrical inner ring and two ribs on the outer ring, making type NU bearings well suited for use as floating bearings
- Enhanced operational reliability
- Long service life

Key Dimensions

Bore (d)	160 mm
O.D. (D)	240 mm 9.4488 in
Width (B)	1.4961 in 38 mm
Dynamic Radial Load Rating - 1M Revs (C1)[1]	276000 N 62000 lbf

Other Dimensions

Weight	5.9 Kg 13 lb
Shaft Backing Shoulder Diameter	174 mm 6.9000 in
Max Shaft Fillet Radius LF ID	1.50 in 0.100 mm
Max Shaft Fillet Radius RF ID	1.5 in 0.100 mm
Max Housing Fillet Radius LF OD	2 in 0.1 mm
Max Housing Fillet Radius RF OD	2 in 0.1 mm
Design Units	Metric
Type	NU

Ratings

Static Radial Load Rating (C0)	367000 N 82500 lbf
Thermal Reference Speed - Grease	2900 rpm
Thermal Reference Speed - Oil[2]	3600 rpm

Factors

Geometry Factor (Cg) [3]	0.1187

[1] Based on 1 x 10^6 L_{10} life for the ISO life calculation method.

[2] See thermal speed ratings in the engineering section.

[3] Geometry constant for Lubrication Life Adjustment Factor a3l.