

The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com (mailto:CustomerCAD@timken.com) • **Web site:** www.timken.com (http://www.timken.com)

Part Number NU1034MA, Cylindrical Roller Radial Bearings - Single Row ISO





Key Dimensions

Bore (d)	170 mm
O.D. (D)	260 mm

	10.2362 in
Width (B)	1.6535 in 42 mm
Dynamic Radial Load Rating - 1M Revs (C1)[1]	321000 N 72200 lbf

Other Dimensions

Weight	8 Kg 17.6 lb
Shaft Backing Shoulder Diameter	186 mm 7.3000 in
Max Shaft Fillet Radius LF ID	2.0 in 0.100 mm
Max Shaft Fillet Radius RF ID	2 in 0.100 mm
Max Housing Fillet Radius LF OD	2 in 0.1 mm
Max Housing Fillet Radius RF OD	2 in 0.1 mm
Design Units	Metric
Type	NU

Ratings

Static Radial Load Rating (C0)	425000 N 95500 lbf
Thermal Reference Speed - Grease	2700 rpm
Thermal Reference Speed - Oil[2]	3300 rpm

Factors

Geometry Factor (Cg) [3]	0.1048

[1] Based on 1 x 10^6 L_{10} life for the ISO life calculation method.

[2] See thermal speed ratings in the engineering section.

[3] Geometry constant for Lubrication Life Adjustment Factor a3l.