

The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com (mailto:CustomerCAD@timken.com) • **Web site:** www.timken.com (http://www.timken.com)

Part Number NU1056MAC4, Cylindrical Roller Radial Bearings - Single Row ISO





Key Features

- High radial load capacity
- Unique brass cage design for demanding applications
- Bearing can be separated for easier mounting and dismounting

- Design has a cylindrical inner ring and two ribs on the outer ring, making type NU bearings well suited for use as floating bearings
- Enhanced operational reliability
- Long service life

Key Dimensions

Bore (d)	280 mm
O.D. (D)	420 mm 16.5354 in
Width (B)	2.5591 in 65 mm
Dynamic Radial Load Rating - 1M Revs (C1)[1]	754000 N 170000 lbf

Other Dimensions

Weight	31 Kg 68.100 lb
Shaft Backing Shoulder Diameter	306.4 mm 12.06 in
Housing Backing Shoulder Diameter	384 mm 15.12 in
Max Shaft Fillet Radius LF ID	3 in 0.100 mm
Max Shaft Fillet Radius RF ID	3 in 0.100 mm
Max Housing Fillet Radius LF OD	3 in 0.1 mm
Max Housing Fillet Radius RF OD	3 in 0.1 mm
Design Units	Metric
Type	NU

Ratings

Static Radial Load Rating (C0)	1080000 N 243000 lbf
Thermal Reference Speed - Grease	1500 rpm
Thermal Reference Speed - Oil[2]	1800 rpm

Factors

Geometry Factor (Cg) [3]	0.1543

[1] Based on 1 x 10^6 L_{10} life for the ISO life calculation method.

[2] See thermal speed ratings in the engineering section.

[3] Geometry constant for Lubrication Life Adjustment Factor a3l.