

The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com (mailto:CustomerCAD@timken.com) • **Web site:** www.timken.com (http://www.timken.com)

Part Number NU2319EMAC3, Cylindrical Roller Radial Bearings - Single Row ISO





Key Features

- High radial load capacity
- Unique brass cage design for demanding applications
- Bearing can be separated for easier mounting and dismounting

- Design has a cylindrical inner ring and two ribs on the outer ring, making type NU bearings well suited for use as floating bearings
- Enhanced operational reliability
- Long service life

Key Dimensions

Bore (d)	95 mm
O.D. (D)	200 mm 7.874 in
Width (B)	2.6378 in 67 mm
Dynamic Radial Load Rating - 1M Revs (C1)[1]	525000 N 118000 lbf

Other Dimensions

Weight	10.4 Kg 22.9 lb
Shaft Backing Shoulder Diameter	116 mm 4.6000 in
Max Shaft Fillet Radius LF ID	2.5 in 0.100 mm
Max Shaft Fillet Radius RF ID	2.5 in 0.100 mm
Max Housing Fillet Radius LF OD	2.5 in 0.1 mm
Max Housing Fillet Radius RF OD	2.5 in 0.1 mm
Design Units	Metric
Type	NU

Ratings

Static Radial Load Rating (C0)	593000 N 133000 lbf

Factors

Geometry Factor (Cg) [2]	0.1095

[1] Based on 1 x 10^6 L_{10} life for the ISO life calculation method.

[2] Geometry constant for Lubrication Life Adjustment Factor a3l.