

The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com (mailto:CustomerCAD@timken.com) • **Web site:** www.timken.com (http://www.timken.com)

Part Number NU240EMAC4, Cylindrical Roller Radial Bearings - Single Row ISO





Key Features

- High radial load capacity
- Unique brass cage design for demanding applications
- Bearing can be separated for easier mounting and dismounting

- Design has a cylindrical inner ring and two ribs on the outer ring, making type NU bearings well suited for use as floating bearings
- Enhanced operational reliability
- Long service life

Key Dimensions

Bore (d)	200 mm
O.D. (D)	360 mm 14.1732 in
Width (B)	2.2835 in 58 mm
Dynamic Radial Load Rating - 1M Revs (C1)[1]	870000 N 196000 lbf

Other Dimensions

Weight	27.40 Kg 60.40 lb
Shaft Backing Shoulder Diameter	217 mm 8.5000 in
Housing Backing Shoulder Diameter	343 mm 13.5000 in
Max Shaft Fillet Radius LF ID	3 in 0.100 mm
Max Shaft Fillet Radius RF ID	3 in 0.100 mm
Max Housing Fillet Radius LF OD	3 in 0.1 mm
Max Housing Fillet Radius RF OD	3 in 0.1 mm
Design Units	Metric
Type	NU

Ratings

Static Radial Load Rating (C0)	1080000 N 243000 lbf
Thermal Reference Speed - Grease	1500 rpm
Thermal Reference Speed - Oil[2]	1800 rpm

Factors

Geometry Factor (Cg) [3]	0.1354

[1] Based on 1 x 10^6 L_{10} life for the ISO life calculation method.

[2] See thermal speed ratings in the engineering section.

[3] Geometry constant for Lubrication Life Adjustment Factor a3l.