

The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com (mailto:CustomerCAD@timken.com) • **Web site:** www.timken.com (http://www.timken.com)

Part Number NU344EMA, Cylindrical Roller Radial Bearings - Single Row ISO





Key Features

- High radial load capacity
- Unique brass cage design for demanding applications
- Bearing can be separated for easier mounting and dismounting

- Design has a cylindrical inner ring and two ribs on the outer ring, making type NU bearings well suited for use as floating bearings
- Enhanced operational reliability
- Long service life

Key Dimensions

Bore (d)	220 mm
O.D. (D)	460 mm 18.1102 in
Width (B)	3.4646 in 88 mm
Dynamic Radial Load Rating - 1M Revs (C1)[1]	1200000 N 270000 lbf

Other Dimensions

Weight	75.90 Kg 167.30 lb
Shaft Backing Shoulder Diameter	240 mm 9.5000 in
Housing Backing Shoulder Diameter	440 mm 17.3000 in
Max Shaft Fillet Radius LF ID	4 in 0.200 mm
Max Shaft Fillet Radius RF ID	4 in 0.2 mm
Max Housing Fillet Radius LF OD	4 in 0.2 mm
Max Housing Fillet Radius RF OD	4 in 0.2 mm
Design Units	Metric
Type	NU

Ratings

Static Radial Load Rating (C0)	1580000 N 355000 lbf
Thermal Reference Speed - Grease	1100 rpm
Thermal Reference Speed - Oil[2]	1200 rpm

Factors

Geometry Factor (Cg) [3]	0.1528

[1] Based on 1 x 10^6 L_{10} life for the ISO life calculation method.

[2] See thermal speed ratings in the engineering section.

[3] Geometry constant for Lubrication Life Adjustment Factor a3l.